

The D-Series consists of robust, reliable and energy-efficient ovens with double temperature sensors to ensure an even heat distribution throughout the oven interior, which gives excellent baking results. The model selection is broad, which makes the series suitable for different types and sizes of bakery. The deck oven is also modular, allowing the possible addition of up to five decks.











## **D-SERIES OPTIONS**

OPTIONS DECK OVEN	D1	D2	D2E	D3	D4
SD Touch II control panel per deck	0	0	0	0	0
D1+ control panel per deck	0	0	0	0	0
Crown height 8.7" per deck (standard 6.3")	0	0	0	0	0
Built-in steam generator with steam trap per deck, 1.8 kW per deck	0	0	0	0	0
Common water connection per deck	0	0	0	0	0
Stone sole per deck	0	0	0	0	0
Door Solid per deck (no window)	0	0	0	0	0
Door Solid high oven chamber per deck (no window)	0	0	0	0	0
Door with double-glazed window per deck	0	0	0	0	0
Door with double-glazed window high oven chamber per deck	0	0	0	0	0
High-temperature model incl. 662°F-proof ceramic glass in doors per deck. Can not be combined with double glass	0	0	0	0	
High-temperature model for high oven chamber incl. 662°F- proof ceramic glass in doors per deck. Can not be combined with double glass	0	0	0	0	
Pull-out shelf	0	0	0	0	
Shelf stand	0	0	0	0	
Canopy	0	0	0	0	0
Stainless steel baking chamber per deck	0	0	0	0	0
Condensation unit with canopy	0	0	0	0	0
IF SEPARATE DECKS ARE ORDERED	D1	D2	D2E	D3	D4
Separate deck section for extension of existing oven	0	0	0	0	0
Extra kit: Top and bottom	0	0	0	0	0
Extra kit: Top and bottom, SD Touch II	0	0	0	0	0
ACCESSORIES	D1	D2	D2E	D3	D4
Setting device	0	0	0	0	0
Transport trolley in s/s with 10 shelves	0	0	0	0	0

OPTIONS DOUBLE DEPTH DECK OVEN	D12ED	D22ED	D32ED	D42ED
SD Touch II control panel per deck	0	0	0	0
D1+ control panel per deck	0	0	0	0
Canopy	0	0	0	0
Door with double-glazed window per deck	0	0	0	0
Solid door per deck (no window)	0	0	0	0
ACCESSORIES	D12ED	D22ED	D32ED	D42ED
Setting device $2 \times 23.6" \times 64.6"$	0	0	0	0
Trolley for Setting device 23.6" $\times$ 64.6"	0	0	0	0

## Standard

O Options